



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/591,688	09/05/2006	Keiko Yamamichi	295714US0PCT	4861

22850 7590 11/19/2010  
OBLON, SPIVAK, MCCLELLAND MAIER & NEUSTADT, L.L.P.  
1940 DUKE STREET  
ALEXANDRIA, VA 22314

EXAMINER
----------

SNYDER, ZACHARY J

ART UNIT	PAPER NUMBER
----------	--------------

2889

NOTIFICATION DATE	DELIVERY MODE
-------------------	---------------

11/19/2010

ELECTRONIC

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

patentdocket@oblon.com  
oblonpat@oblon.com  
jgardner@oblon.com

<b>Office Action Summary</b>	<b>Application No.</b> 10/591,688	<b>Applicant(s)</b> YAMAMICHI ET AL.	
	<b>Examiner</b> Zachary Snyder	<b>Art Unit</b> 2889	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

#### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

#### Status

- 1) ☒ Responsive to communication(s) filed on 26 August 2010.
- 2a) ☒ This action is **FINAL**.                      2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

#### Disposition of Claims

- 4) ☒ Claim(s) 2,3,6-11,13,15 and 22-31 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 2,3,6-11,13,15 and 22-31 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

#### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

#### Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All    b) ☐ Some \*    c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

#### Attachment(s)

- |   |   |
|---|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892)                    | 4) <input type="checkbox"/> Interview Summary (PTO-413)           |
| 2) <input type="checkbox"/> Notice of Draftperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____                                      |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)         | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(s)/Mail Date _____   | 6) <input type="checkbox"/> Other: _____                          |

## **DETAILED ACTION**

### ***Response to Amendment***

Receipt is acknowledged of applicant's amendment filed 8/26/2010. Claims 2-3, 6-11, 13, 15, 22-31 are pending and an action on the merits is as follows.

### ***Response to Arguments***

Applicant's arguments filed 8/26/2010 have been fully considered but they are not persuasive.

Applicant argues that:

(1) The Examiner does not explain why the alternate embodiment disclosed by Winters et al. would be used for only one gamut pixel but not for all of them.

(2) The references of Winters et al. and Kim are for an OLED and LCD device respectively and one of ordinary skill in the art would not combine the two references.

(3) Kim teaches away from using two types of metal oxide layers.

In response:

(1) The Examiner does not state that the teachings of Winters in COL. 7, LINES 51-55 would only be present in one gamut pixel. The reference to COL. 7 LINES 51-55 was to show that the separate electrode is present in the one gamut pixel to meet the limitations of the claim but does not state that it is only formed in this gamut pixel.

(2) Although LCD and OLED devices rely on two different types of technology, the electrode structure in the two devices are very similar. One of ordinary skill in the art would be able to use the teachings of LCD TFT technology within the art of OLED TFT formation.

Art Unit: 2889

(3) The claims as written do not state that two different types of metal oxide layers are used but rather that the crystallinity is different between the two layers.

***Claim Rejections - 35 USC § 103***

Claims 2-3, 6-11, 13, 15, 22-31 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent 7,030,553 B2 to Winters et al. in view of U.S. PG Publication 2003/0184688 A1 to Kim.

In regard to claim 2, Winters discloses (figure 3 for reference) an organic electroluminescent display comprising:

a substrate (substrate 100, COL. 4, LINES 53-54); and

a first organic electroluminescent device part (gamut subpixel 21b) and a second organic electroluminescent (gamut subpixel 21a) device part placed side by side on a surface of the substrate (shown in figure 3);

the first organic electroluminescent device part (gamut subpixel 21b) including at least a light reflective conductive layer (reflector 150b; the teachings of figure 3 can be applied to passive matrix display (COL. 4, LINES 8-12) where a conductive material would be used as the reflector so it can function as an electrode (COL. 4, LINES 34-37)), a first metal oxide layer (transparent cavity-spacer layer 140b, COL. 5, LINE 66), an organic luminescent medium layer (organic EL media 210, COL. 7, LINE 23), and a transparent electrode layer (transparent electrode 240, COL. 7, LINE 45) in this order (shown in figure 3) and including a light reflective

Art Unit: 2889

layer (semi-transparent reflector 230, COL. 7, LINES 40-41) inside or outside of the organic luminescent medium layer or the transparent electrode layer;

the second organic electroluminescent device part (gamut subpixel 21a) including at least a light reflective conductive layer (reflector 150a; the teachings of figure 3 can be applied to passive matrix display (COL. 4, LINES 8-12) where a conductive material would be used as the reflector so it can function as an electrode (COL. 4, LINES 34-37)), a first metal oxide layer (transparent cavity-spacer layer 140a), a second metal oxide layer (a second metal oxide layer can be formed above the reflector 150a and below the organic EL media layer, COL. 7, LINE 51-56), an organic luminescent medium layer (organic EL media 210, COL. 7, LINE 23), and a transparent electrode layer (transparent electrode 240, COL. 7, LINE 45) in this order (shown in figure 3) and including a light reflective layer (semi-transparent reflector 230, COL. 7, LINES 40-41) inside or outside of the organic luminescent medium layer or the transparent electrode layer; and

an emission spectrum of light from the first organic electroluminescent device part differing from an emission spectrum of light from the second organic electroluminescent device part (gamut subpixels 21a and 21b have the colors red and blue respectively, COL. 3, LINES 24-26).

Winters does not disclose that the second metal oxide layer is able to be etched more easily than the first metal oxide layer.

Kim teaches a method for selectively etching an metal oxide pixel layer to form areas of varying thickness wherein a first portion is a crystalline layer (layer 108b, figure 3b) and a

Art Unit: 2889

second and third portion are amorphous (108a, figure 3b) so that the amorphous section is selectively etched away.

At the time of the invention, it would have been obvious to one of ordinary skill in the art, having the teachings of Winters and Kim before him or her, for the height controlling layer of the electrode (the second metal oxide layer of Winters) to be more easily etched as taught by Kim so that the electrode can be selectively etched and form a pixel electrode of varying heights in a micro-cavity display device.

In regard to claim 3, Winters discloses (figure 3 for reference) an organic electroluminescent display comprising:

a substrate (substrate 100, COL. 4, LINES 53-54); and

a first organic electroluminescent device part, a second organic electroluminescent device part, and a third organic electroluminescent device part placed side by side on a single surface of the substrate (gamut subpixels 21(a, b, and c);

the first organic electroluminescent device part (gamut subpixel 21c) including at least a light reflective conductive layer (reflector 150c; the teachings of figure 3 can be applied to passive matrix display (COL. 4, LINES 8-12) where a conductive material would be used as the reflector so it can function as an electrode (COL. 4, LINES 34-37)), an organic luminescent medium layer (organic EL media 210, COL. 7, LINE 23), and a transparent electrode layer (transparent electrode 240, COL. 7, LINE 45) in this order and including a light reflective layer (semi-transparent reflector 230, COL. 7, LINES 40-41) inside or outside of the organic luminescent medium layer or the transparent electrode layer (shown in figure 3);

Art Unit: 2889

the second organic electroluminescent device part (gamut subpixel 21b) including at least a light reflective conductive layer (reflector 150b), a first metal oxide layer (cavity-spacer 140b), an organic luminescent medium layer (organic EL media 210), and a transparent electrode layer (transparent electrode 240) in this order and including a light reflective layer (semi-transparent reflector 230) inside or outside of the organic luminescent medium layer or the transparent electrode layer (shown figure 3);

the third organic electroluminescent device part (gamut subpixel 21a) including at least a light reflective conductive layer (reflector 150a), a first metal oxide layer (cavity-spacer 140a), a second metal oxide layer (a second metal oxide layer can be formed above the reflector 150a and below the organic EL media layer, COL. 7, LINE 51-56), an organic luminescent medium layer (organic EL media 210), and a transparent electrode layer (transparent electrode 240) in this order and including a light reflective layer (semi-transparent reflector 230) inside or outside of the organic luminescent medium layer or the transparent electrode layer; and

emission spectra of light from the first, second, and third organic electroluminescent device parts differing from one another (gamut subpixels 21a, 21b, and 21c have the colors red, blue, and green respectively, COL. 3, LINES 24-26).

Winters does not disclose that the second metal oxide layer is able to be etched more easily than the first metal oxide layer.

Kim teaches a method for selectively etching an metal oxide pixel layer to form areas of varying thickness wherein a first portion is a crystalline layer (layer 108b, figure 3b) and a second and third portion are amorphous (108a, figure 3b) so that the amorphous section is selectively etched away.

Art Unit: 2889

At the time of the invention, it would have been obvious to one of ordinary skill in the art, having the teachings of Winters and Kim before him or her, for the height controlling layer of the electrode (the second metal oxide layer of Winters) to be more easily etched as taught by Kim so that the electrode can be selectively etched and form a pixel electrode of varying heights in a micro-cavity display device.

In regard to claim 6, Winters in view of Kim teaches the limitations of claim 2 and Kim also teaches that the first metal oxide layer and the second metal oxide layer include an metal oxide (ITO, paragraph 27), and crystallinity of the first metal oxide layer is higher than crystallinity of the second metal oxide layer (one is amorphous and one is polycrystalline, paragraph 27). The motivation to combine is the same as discussed in regard to claim 2.

In regard to claim 7, Winters in view of Kim teaches the limitations of claim 2 and Kim also teaches that the first metal oxide layer is crystalline, and the second metal oxide layer is non-crystalline (one is amorphous and one is polycrystalline, paragraph 27). The motivation to combine is the same as discussed in regard to claim 2.

In regard to claim 8, Winters in view of Kim teaches the limitations of claim 6 and that at least one of the first metal oxide layer (transparent cavity-spacer layer 140b, COL. 5, LINE 66) and the second metal oxide layer includes an oxide of an element selected from the group consisting of In, Sn, Zn, Ce, Sm, Pr, Nb, Tb, Cd, Ga, Al, Mo, and W (ITO, COL. 6, LINE 37).



Art Unit: 2889

In regard to claim 9, Winters in view of Kim teaches the limitations of claim 6 and that at least one of the first metal oxide layer (transparent cavity-spacer layer 140b, COL. 5, LINE 66) and the second metal oxide layer includes an oxide of an element selected from the group consisting of In, Sn, and Zn (ITO, COL. 6, LINE 37).

In regard to claim 10, Winters in view of Kim teaches the limitations of claim 2 and that the light reflective conductive layer (reflector 150b, COL. 7, LINE 31) includes a metal selected from the group consisting of Al, Ag, Au, Pt, Cu, Mg, Cr, Mo, W, Ta, Nb, Li, Mn, Ca, Yb, Ti, Ir, Be, Hf, Eu, Sr, Ba, Cs, Na, and K, or an alloy containing at least one metal selected from the group (preferred materials are Ag, Au, or alloys composed of one or both of these materials, COL. 4, LINES 28-30).

In regard to claim 11, Winters in view of Kim teaches the limitations of claim 2 and that the light reflective conductive layer (reflector 150b, COL. 7, LINE 31) includes one, or two or more metals selected from the group consisting of Al, Ag, Au, Pt, Cu, Mg, Cr, Mo, W, Ta, Nb, Li, Mn, Ca, Yb, Ti, Ir, Be, Hf, Eu, Sr, Ba, Cs, Na, and K, or an alloy containing at least one metal selected from the group (preferred materials are Ag, Au, allows it to be composed of one or both of these materials, COL. 4, LINES 28-30).

In regard to claim 13, Winters in view of Kim teaches the limitations of claim 2 and that the display further comprises a color filter (COL. 3, LINES 62-67).

Art Unit: 2889

In regard to claim 15, Winters in view of Kim teaches the limitations of claim 2 and Kim teaches that the method further comprises:

selecting, as a material of a second metal oxide layer, a material that has a lower crystallinity than a crystallinity of a first metal oxide layer (layer 108a is amorphous and layer 108b is polycrystalline); and that the layers are then wet etched (amorphous layer is etched using an etchant such as diluted oxalic acid, paragraph 50).

When forming the structure of Winters using the selective etching method taught by Kim, the second metal oxide layer would be formed after forming the first metal oxide layer. The motivation to combine is the same as discussed in regard to claim 2.

In regard to claim 22, Winters in view of Kim teaches the limitations of claim 3 and Kim also teaches that the first metal oxide layer and the second metal oxide layer include an metal oxide (ITO, paragraph 27), and crystallinity of the first metal oxide layer is higher than crystallinity of the second metal oxide layer (one is amorphous and one is polycrystalline, paragraph 27). The motivation to combine is the same as discussed in regard to claim 2.

In regard to claim 23, Winters in view of Kim teaches the limitations of claim 3 and Kim also teaches that the first metal oxide layer is crystalline, and the second metal oxide layer is non-crystalline (one is amorphous and one is polycrystalline, paragraph 27). The motivation to combine is the same as discussed in regard to claim 2.

Art Unit: 2889

In regard to claim 24, Winters in view of Kim teaches the limitations of claim 22 and that at least one of the first metal oxide layer (transparent cavity-spacer layer 140b, COL. 5, LINE 66) and the second metal oxide layer includes an oxide of an element selected from the group consisting of In, Sn, Zn, Ce, Sm, Pr, Nb, Tb, Cd, Ga, Al, Mo, and W (ITO, COL. 6, LINE 37).

In regard to claim 25, Winters in view of Kim teaches the limitations of claim 22 and that at least one of the first metal oxide layer (transparent cavity-spacer layer 140b, COL. 5, LINE 66) and the second metal oxide layer includes an oxide of an element selected from the group consisting of In, Sn, and Zn (ITO, COL. 6, LINE 37).

In regard to claim 26, Winters in view of Kim teaches the limitations of claim 3 and that the light reflective conductive layer (reflector 150b, COL. 7, LINE 31) includes a metal selected from the group consisting of Al, Ag, Au, Pt, Cu, Mg, Cr, Mo, W, Ta, Nb, Li, Mn, Ca, Yb, Ti, Ir, Be, Hf, Eu, Sr, Ba, Cs, Na, and K, or an alloy containing at least one metal selected from the group (preferred materials are Ag, Au, or alloys composed of one or both of these materials, COL. 4, LINES 28-30).

In regard to claim 27, Winters in view of Kim teaches the limitations of claim 3 and that the light reflective conductive layer (reflector 150b, COL. 7, LINE 31) includes one, or two or more metals selected from the group consisting of Al, Ag, Au, Pt, Cu, Mg, Cr, Mo, W, Ta, Nb, Li, Mn, Ca, Yb, Ti, Ir, Be, Hf, Eu, Sr, Ba, Cs, Na, and K, or an alloy containing at least one

Art Unit: 2889

metal selected from the group (preferred materials are Ag, Au, allows it to be composed of one or both of these materials, COL. 4, LINES 28-30).

In regard to claim 28, Winters in view of Kim teaches the limitations of claim 3 and that the display further comprises a color filter (COL. 3, LINES 62-67).

In regard to claim 29, Winters in view of Kim teaches the limitations of claim 3 and Kim teaches that the method further comprises:

selecting, as a material of a second metal oxide layer, a material that has a lower crystallinity than a crystallinity of a first metal oxide layer (layer 108a is amorphous and layer 108b is polycrystalline); and that the layers are then wet etched (amorphous layer is etched using an etchant such as diluted oxalic acid, paragraph 50).

When forming the structure of Winters using the selective etching method taught by Kim, the second metal oxide layer would be formed after forming the first metal oxide layer. The motivation to combine is the same as discussed in regard to claim 2.

In regard to claims 30 and 31, Winters in view of Kim teach the limitations of claim 2 and 3, and Kim also teaches that the more easily etched layer (film 108a, comprises indium zinc oxide, paragraph 48, corresponding to the second metal oxide) and the not easily etched layer (108b, corresponding to the first metal oxide, comprises ITO, paragraph 49). The motivation to combine is the same as discussed in regard to claims 2 and 3.

***Conclusion***

Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Zachary Snyder whose telephone number is (571)270-5291. The examiner can normally be reached on Monday through Thursday, 7:30AM to 6PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Toan Ton can be reached on (571)272-2303. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2889

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Toan Ton/  
Supervisory Patent Examiner, Art Unit 2889

/Zachary Snyder/  
Examiner, Art Unit 2889